

**TENSIOL RWS**  
*SPECIFIC CONCENTRATED DETERGENT  
FOR VACUUM SEALED HIDES*

**CHEMICAL COMPOSITION**

Surfactants chemically stabilized with alkaline substances

**CHARACTERISTICS**

<i>Apparence:</i>	<i>yellowish liquid</i>
<i>pH in solution at 10%:</i>	<i>12</i>
<i>Ionic charge:</i>	<i>nonionic</i>

**PROPERTIES**

**TENSIOL RWS** is a specific concentrated degreasing product for the determinant cleaning of the metal grills of the vacuum sealed hide drying system.

It is well known that rough or sporadic maintenance of such important components is the cause of serious inconveniences such as:

- Accumulation of dangerous layer constituted of colourants and poorly fixed greases.
- Blockage of the grills also caused by the deposit of dust and fragments of hide.

The most serious and frequent consequences are:

- Accumulation of indelible marks on the dried hides, specially if they are clear or a pastel tint.
- Poor functioning of the installation with a consequent overloading of the pumping system when empty.

**CONTINUE**

Our suggestions for the use of the products correspond to our present knowledge. They do not release the purchaser in any way whatsoever from the responsibility of carrying out their own tests to establish the suitability of the products supplied in relation to the results that are to be obtained. The usage methods of the products are not within our control and therefore become the complete responsibility of the purchaser. We guarantee the quality of our products in respect of the general sales and supply terms and conditions.

## USAGE METHOD

**TENSIOL RWS** can be used in three distinct ways:

- Total and complete cleaning of the grills: this operation is effectuated twice a year, disassembling the extraction hood and treating it with a solution of 8 – 10% of **TENSIOL RWS** nebulized and/or sprayed at high pressure via a water jet machine and terminating the treatment with a rapid rinse.
- Maintenance cleaning: between the drying out of one lot of dark hides and one lot of clear hides, nebulize the said washing solution and rerinse with lukewarm water.
- In depth maintenance cleaning: pour out a solution of 5% **TENSIOL RWS** that is sufficient enough to cover the whole metal surface where the hide is placed;

Briefly activate the pumping system whilst empty in such a way as to completely soak the grills. Switch off the machine: overnight, the washing solution will completely emulsify the accumulated grease. In the morning, operate an energetic washing, spraying hot water at high pressure.

### PRECAUTIONS FOR USE:

**TENSIOL RWS** contains sodium hydroxide and therefore in the preparation of the solutions always add the substance to the water and not conversely, for avoid formation of corrosive splashes due to the temperature. Attention: attacks aluminium, tin, lead, zinc; It reacts violently with acids. Follow the recommended dilutions.